

# RSA215EK

21.5" Full IP66/ IP69K  
Stainless Panel PC



**RSA215EK-CJ**



**RSA215EK-EL**

## Specification

### Display + Touch

Panel	21.5"
Resolution	1920 x 1080
Brightness	500 nits
View Angle	89/ 89/ 89/ 89
Touch	PCAP/ RTP

### System

	RSA215EK-CJ	RSA215EK-EL
Processor	Intel Celeron J1900	Intel Elkhart Lake J6412
Memory	4GB Memory (Up to 8GB)	4GB Memory (Up to 8GB)
Storage	64GB M.2 SATA SSD 128GB SSD (Optional)	64GB M.2 SATA SSD 128GB SSD (Optional)
Watchdog	Support	Support
OS	Win 10 IoT Linux Ubuntu	Win 10 IoT Linux Ubuntu

### I/O Port

	RSA215EK-CJ	RSA215EK-EL
USB	1 x M12 USB 2.0 2 x M12 USB 2.0 (Optional)	1 x M12 USB 3.0 2 x M12 USB 3.0 (Optional)
LAN	1 x M12 LAN (Optional 2 LAN)	1 x M12 LAN (Optional 2 LAN)
COM port	1 x M12 RS232 Comport	1 x M12 RS232 Comport

### Buttons

Power Button	1 x Power Button
Touch Power	1 x Touch Power Button (On the side)

### Power

Power Input	1 x M12 connector 12V DC (Optional 9~36V)
Power Consumption	MAX. 15W

### Mechanical

Material	316/ V4L Stainless Housing (Optional 314/ V2L)
Mounting	VESA Mount (YOKE Mount Optional)

### Reliability

Operating Temp.	0°C ~ 60°C with air flow
Storage Temp.	-20°C ~ 70°C
Humidity	10% ~ 90%, non-condensing

### Accessory (Optional)

Power Adapter	12V 50W
External M12 Cable	1 x External M12 LAN Cable 1 x External M12 COMport Cable 1 x External M12 USB Cable 1 x External M12 Power Cable